


ITEMS		SPECIFICATION OF NEW MODEL		
		AW-DK1775WUPBB		
Picture Appearance				
Color code		WK		
Destination		Saudi Arabia		
Customer		ALJ		
Rated Voltage		220-230VAC 60Hz		
Product Standard	(Safety requirements)	IEC/SASO Registration statement		
	(EMF requirements)	-		
	(EMC requirements)	-		
	(Energy Saving)	SASO EE Registration		
	(Water Saving)	-		
Dimension	Product size (R*S*C) (W*D*H)	W 650 x D 655 x H 1052 (Not including drain hose & inlet hose) W 690 x D 700 x H 1100 (Including drain hose & inlet hose)		
	Cabinet size	W 640 x D 640		
	Packing size	W 705 x D 715 x H 1150		
Weight Product	Net weight	49 kg		
	- Pump	●		
	- Stand	-		
	Gross weight	55 kg		
Loading Q'ty	40ft	102 sets		
Load capacity	Wash	15.0 kg		
	Spin	15.0 kg		
Power input	Wash	480 W		
	Spin	160 W		
Water amount	High level	105 liters		
	Low level	25 liters		
Water consumption (High level) Regular cycle		195 liters		
Rated period of operation	Wash only	16 min.		
	Regular Course cycle	68 min.		
Features	Structure	S-DD Inverter motor	●	(Same current)
		Stainless steel basket	●	(Same current)
		Magic drum	-	(None)
		Glass Lid	-	(None)
		See through lid	●	(Same current)
		Cabinet base	●	(Same current)
		Filter	●	Cassette lint filter
		Inlet Valve	●	(2 Port-Upper side)
		Drain Pump	●	(Have)
		Lid lock	●	(Lock from start to operation)
	Function	Water flow Power	●	(5 Level: Low-High)
		Resume function	●	
		Zero standby power	●	
		Preset Time	●	
		Child proof	●	
		Drum LED-Light	-	(None)
		Tub Dry	●	
		Super spin dry	●	Circular intake[30 / 60 / 90 min]
	Performance	Hydro twin power	●	
Wash temperature		●	Hot / Warm / Cold	
Roller unit		-	(None)	
Pulsator		●	(Same current)	

		Washing system	●	(Same current)
		UFB Operation	●	(Included)
Washing course	Regular		●	
	Soak		●	(Support: Energy Efficiency)
	Heavy wash		●	
	Memory		●	
	Delicate		●	
	Blanket		●	
	Fragrance		●	
	Speed		●	
	Tub clean		●	
Wash (Pulsator)	Diameter		φ	420 mm Pulsator ID
	Rotation (rpm)	50/60 Hz		70-150 rpm (Variable)
Spin (Basket)	Diameter	L1	φ	522 mm Spin basket ID
		L2	φ	440 mm Balance Ring ID
	Height	H1		502 mm
		H2		418 mm
	Spin basket volume	L1+L2		98 liters
	Rotation (rpm)	50/60 Hz		700 rpm
Printing part & Language	Panel plate			English/Arabic
	Indicate Capacity			-
	Tokyo Japan			-
	Owner's manual			English/Arabic
	Name plate			Arabic
	Carton box			English
Accessories parts	Water supply hose		●	[Hot & Cold]
	Drain hose		-	
	Pump drain hose		●	
	Hose stopper		●	
	Cabinet cover (Rat guard)		-	
	Inlet Clamp		●	
	Leg cap		-	
Plug type				Type G (3P)
Power cord				3 wires
Outer Earth wire				-

