


ITEMS		SPECIFICATION OF NEW MODEL	
		AW-DUK2217WUPBB	
Picture Appearance			
Color code		SS	
Destination		Saudi Arabia	
Customer		ALJ	
Rated Voltage		220-230VAC 60Hz	
Product Standard	(Safety requirements)	IEC/SASO Standard (CB certificate)	
	(EMF requirements)	-	
	(EMC requirements)	-	
	(Energy Saving)	SASO standard (EER & Registrarion)	
	(Water Saving)	-	
Dimension	Product size	W 650 x D 663 x H 1061 (Not including drain hose & inlet hose)	
	(W*D*H)	W 685 x D 710 x H 1061 (Including drain hose & inlet hose)	
	Cabinet size	W 640 x D 640	
	Packing size	W 695 x D 740 x H 1150	
Weight Product	Net weight	54 kg	
	- Pump	-	
	- Stand	-	
	Gross weight	60 kg	
Loading Q'ty	40ft	102 sets	
Load capacity	Wash	15.0 kg	
	Spin	15.0 kg	
Power input	Wash	(385 W)	
	Spin	(145 W)	
Water amount	High level	105 liters	
	Low level	25 liters	
Water consumption	(High level) Regular cycle	(195 liters)	
Rated period of operation	Wash only	(15 min)	
	Regular Course cycle	(65 min)	
Features	Structure	S-DD Inverter motor	●
		Stainless steel basket	●
		Magic drum	-
		Glass Lid	●
		See through lid	●
		Cabinet base cover	●
		Filter	●
		Inlet Valve	●
		Lid lock	●
	Function	Water flow Power	●
		Resume function	●
		Zero standby power	●
		Preset Time	●
		Child proof	●
		Drum LED-Light	-
		Tub Dry	●
		Super spin dry	●
	Performance	Hydro twin power	●
		Wash temperature	●
		Roller unit	●
		Pulsator	●
Washing system		●	
	UFB Wash operation	-	

Washing course	Regular		●	
	Soak		●	
	Heavy wash		●	
	Delicate		●	
	Blanket		●	
	Fragrance		●	
	Speed		●	
	Tub clean		●	
Wash (Pulsator)	Diameter		φ 420 mm	Pulsator ID
	Rotation (rpm)	50/60 Hz	70-150 rpm	(Variable)
Spin (Basket)	Diameter	L1	φ 522 mm	Spin basket ID
		L2	φ 440 mm	Balance Ring ID
	Height	H1	502 mm	
		H2	418 mm	
	Rotation (rpm)	50/60 Hz	700 rpm	
Printing part & Language	Panel plate		English/Arabic	
	Indicate Capacity		-	
	Tokyo Japan		-	
	Owner's manual		English/Arabic	
	Name plate		Arabic	
	Carton box		English	
Accessories parts	Water supply hose		●	[Hot & Cold]
	Drain hose		-	
	Pump drain hose		●	
	Hose stopper		●	[with pump hose]
	Cabinet base cover (Rat guard)		●	
	Leg cap		-	
Plug type		Type G (3P)		
Power cord		3 wires		
Outer Earth wire		-		

