


| | |
|---|---|
| Model number | DWD40TBS,(TY-LWYR79T) |
| Product photos |  |
| Features | <ol style="list-style-type: none"> 1.The newest slim bottom loading design 2. Stainless steel decoration and door 3. Piano press button on the top 4. Child safety lock for hot water faucet 5. With stainless steel water tank 6. Big cooling capacity to 4L/h |
| Cabinet/refrigerator | / |
| Voltage/Frequency | 220-240V~ 50/60Hz |
| Cooling Method | Compressor cooling |
| Heating Method | Electric |
| Compressor Coil material | Aluminum coil |
| Refrigant type and weight | R134a, 42g |
| Sound (dBA) | 55 |
| IP code | IPX0 |
| Functional description parameters | |
| Heated water temperature -(°C) | ≥90°C |
| Heated water capacity min at 25 (°C) Ambient (L/hr) | 5L |
| Chilled water temperature - nominal - (°C)/ | ≤10°C |
| Chilled water capacity min at 25 (°C) Ambient | 4L |
| heating watts (W) | 420W |
| Cooling watts (W) | 100W |
| Water Supply | Bottle water |
| Chilled water | √ |
| Room Temperature Water | √ |
| Hot Water | √ |
| Typical Operating Ambient Temperature (°C) / (°F) | 10-43°C |
| Operating Humidity | ≤90% |
| Water Spouts | one |
| Water bottle position | bottom loading |
| Cold water tank material | SUS304 |
| Hot water tank material | SUS304 |
| Hot Tank dimension (ID X length) mm | 0.8L |
| Hot water pipeline | Silicon tube |
| Cold Tank dimension (ID X length) mm | 3.5L |
| Cold water pipeline | Silicon tube |
| Packaging information | |
| N.W. (kg) | 15 |
| G.W. (kg) | 17 |
| Product Dimensions (mm) | 310*357*1086mm |
| Packing Dimensions (mm) | 372*407*1146mm |
| Loading Capacity | |

| | |
|------|--------|
| 40HQ | 405pcs |
|------|--------|