

Model	YL1516S
Loading type	Bottom Loading
Product Dimensions(mm)	310*360*1040
Voltage/Frequency	220~240V/50~60Hz
Cooling Method	Compressor
Heating Method	Internal Element
Refrigant type and weight	R134a/32g
Sound (dBA)	≤55dB
Heated water temperature - (° C)	≥85°C
Heated water capacity min at 25 (° C) Ambient (L/hr)	4L/H
Chilled water temperature - nominal - (° C)	≤10°C
Chilled water capacity min at 25 (° C) Ambient (L/hr)	4L/H
heating watts (W)	420W
Cooling watts (W)	100W
Water Supply	Bottle Water
Chilled water	≥1.2L/Min
Room Temperature Water	≥1.0L/Min
Hot Water	≥1.2L/Min
Chilled water	Y
Ambient water	Y
Hot Water	Y
Water Spouts	3
Water bottle position	Bottom Load
Cold water tank material	SUS304
Hot water tank material	SUS304
Hot Tank dimension (ID X length) mm	φ100 *148(1.16L)
Hot water pipeline	silicone tube
Cold Tank dimension (ID X length) mm	φ160 *183(3.6L)
Cold water pipeline	silicone tube
Packaging information..	
Product Dimensions(mm)	310*360*1040
Packing Dimensions(mm)	358*386*1120
Loading Capacity..	
20°GP	192
40°GP	396
40°HQ(No 3rd layer loading)	396
40HQ(with the 3rd layer Horizontal loading)	456